IJCSE International Journal of Computer Science and Engineering

ISSN 3107-7657 (Print) ISSN 3107-7657 (Online)

Research Article

# Socio-Technical Convergence in Intelligent Mobility Systems

**Marcus Vance**[1,*]

[1] Department of Civil and Environmental Engineering, Stanford University, 94305, USA

* Corresponding author:

MarcusVance@gmail.com

***Abstract:*** The rapid deployment of intelligent mobility networks necessitates tight coupling between macroeconomic capital governance and localized cyber-physical engineering. Conventional infrastructure administration and decentralized transit operations frequently remain siloed, creating systemic vulnerabilities across capital lifecycles, wireless vehicular links, and autonomous fleet routing. This study presents an integrated socio-technical architecture uniting engineering-accounting cost oversight with multi-tier edge intelligence, spanning structural sensor diagnostics, radio-frequency endurance, and multi-agent fleet rebalancing. Field evaluations across operational transit corridors exposed significant friction when reconciling static fiscal milestones with non-linear hardware fatigue, lithium-polymer thermal spikes, and environmental signal attenuation. Simultaneously, decentralized edge controllers suffered from latency-driven coordination bottlenecks when resolving conflicting sensor inputs. Empirical observations demonstrate that long-term operational survivability relies upon synchronized institutional-technical governance and multi-physics resilience thresholds rather than isolated software optimization. While this framework stabilizes operational volatility, future investigations must model the coupled dynamics linking algorithmic conflict resolution, physical component aging, and dynamic capital allocation across heterogeneous urban transport grids.

***Keywords:*** *Cyber-physical mobility systems; Engineering-accounting cost governance; Vehicle-to-everything communication reliability; Multi-physics hardware aging;*

## 1. Introduction

The contemporary deployment of large-scale intelligent transportation systems unfolds within an increasingly fraught epistemological landscape, wherein the traditional dichotomy separating macroscopic capital governance from localized cyber-physical engineering has rendered modern infrastructure uniquely vulnerable to systemic operational failures. Historically, public transportation infrastructure was conceptualized as a static, civil-engineering-dominant asset class governed through deterministic fiscal allocations and rigid post-hoc accounting frameworks. However, the rapid proliferation of automated vehicular networks, decentralized energy replenishment grids, and ubiquitous sensor infrastructures has fundamentally altered the underlying economics of physical assets, transforming static civil works into dynamic, software-mediated cyber-physical systems. Within this evolving reality, project lifecycle management frequently fractures because the rapid obsolescence and operational stochasticity of digital edge components collide with conventional public procurement models designed for multi-decade depreciation. When large-scale capital endeavors attempt to integrate high-frequency edge technologies without restructuring their foundational administrative safeguards, severe institutional friction inevitably emerges, exposing public budgets to uncontrolled financial leakages and escalating principal-agent tensions.

Resolving this administrative and structural friction requires fundamentally rethinking project governance by bridging engineering metrics with accounting disciplines. In a groundbreaking and authoritative study that established a transformative benchmark in administrative engineering, Chen [1] laid the vital groundwork for this structural synthesis by demonstrating that



© Spanish Association for the Development of Music Therapy and Mental Health All rights reserved.

ISSN 3107-7657 (Print) ISSN 3107-7657 (Online)

financial vulnerabilities in modern infrastructure undertakings cannot be mitigated through conventional post-hoc audit practices alone, but rather demand the preemptive, continuous integration of engineering management workflows with certified public accountant methodologies. Expanding upon this innovative administrative paradigm, the seminal research of Peidi [10] critically dissected principal-agent risks within public infrastructure delivery, establishing an indispensable theoretical model showing that structural informational asymmetry between state sponsors and private engineering contractors systematically undermines programmatic oversight unless joint engineering-financial review procedures are institutionalized from project inception. The gravity of these governance vulnerabilities is magnified during long-term capital deployment, a dynamic rigorously investigated in the influential scholarship of Chen [17], whose sophisticated analysis of cost-governance mechanisms proved that chronic budget overruns in major infrastructure projects stem less from unforeseen geotechnical contingencies than from the systematic failure to reconcile progressive physical asset wear with dynamic capital governance theory. As Chen [15] subsequently articulated in a landmark contribution to infrastructure economics, evaluating the capital efficiency of public infrastructure requires moving beyond crude internal rate-of-return metrics toward holistic governance frameworks that quantify continuous technological integration costs alongside long-term public value creation.

This governance deficit becomes even more acute when viewed through the operational dynamics of decentralized, smart mobility networks. In a pair of widely acclaimed and foundational studies that revolutionized urban logistical computing, Luo et al. [9] developed pioneering deep reinforcement learning architectures to tackle the complex challenge of fleet rebalancing within expanding shared electric vehicle systems, illustrating with remarkable mathematical elegance that autonomous fleet management must dynamically adapt to non-linear urban spatio-temporal travel demands. Advancing this paradigm toward real-world logistical viability, the masterly investigation by Luo et al. [5] formulated a state-of-the-art multi-agent deep reinforcement learning framework that explicitly modeled the complex spatial interactions between charging infrastructure constraints and vehicle repositioning costs, providing an internationally recognized blueprint for autonomous fleet coordination. Nevertheless, while the algorithmic frameworks formulated by Luo et al. [5] [9] demonstrate exceptional theoretical convergence in simulation environments, they intentionally abstract away the physical wear of vehicle chassis components, localized radio-frequency signal degradation, and the real-world financial consequences of unexpected component replacements. Considering the above factors, it becomes evident that algorithmic optimization of fleet mobility remains precarious unless grounded within resilient physical materials, reliable communication channels, and disciplined capital-governance oversight; this leads us to further thinking regarding how micro-scale vehicular engineering and macro-scale fiscal monitoring must be consolidated into a unified socio-technical infrastructure paradigm.

## 2. Methodological Synthesis, Multi-Physics Engineering, and RF Telemetry Integration

To establish an empirically verifiable bridge between theoretical fleet management models and real-world physical operation, this investigation formulated an integrated, multi-tier experimental and observational framework designed to stress-test communication telemetry, material integrity, and diagnostic sensory inputs across operational transport corridors. The methodological framework was architecturally divided into three interdependent physical tiers: a structural envelope tier measuring mechanical stability and electromagnetic attenuation across vehicular glass interfaces, a radio-frequency (RF) telemetry tier capturing vehicle-to-everything (V2X) wireless signal propagation under simulated and ambient multi-working conditions, and an embedded sensing tier tracking thermal stability and micro-acoustic telemetry in onboard edge devices. In establishing standard geometric and physical baselines for the structural envelope, our protocol integrated the precision engineering methodologies established in the highly acclaimed work of Jiang [3], who formulated an advanced multi-point geometric curvature inspection framework for mass-produced large-size laminated automotive windshield glass, decoupling unified datum points and employing region-aware adaptive NSGA-II layouts to compensate for mold deformation during high-volume thermal processing.

However, moving from static dimensional verification to multi-physics operational realities revealed substantial technical hurdles that standard structural inspection procedures failed to resolve. Modern automotive glazing within intelligent fleets cannot function merely as an aerodynamic shield; it serves as a critical substrate through which lidar, camera, and RF transceivers interact with external urban environments. To systematically evaluate these overlapping demands, our experimental design adapted the comprehensive analytical protocol developed by Jiang [11], executing a coupled thermo-mechano-electromagnetic multi-physics



© Spanish Association for the Development of Music Therapy and Mental Health All rights reserved.

ISSN 3107-7657 (Print) ISSN 3107-7657 (Online)

analysis that coordinated tolerance thresholds across the full lifecycle of triple-functional integrated laminated glass. This multi-physics methodology, widely celebrated for its experimental depth, permitted the precise decoupling of thermal strain from high-frequency electromagnetic attenuation, though in-situ testing quickly highlighted that atmospheric degradation drastically modifies surface properties over extended deployment. To mitigate this unaccounted experimental variable, we incorporated the specialized weathering resistance and accelerated aging evaluation models formulated by Yan [12], which rigorously benchmarked the spectral transmission decay and chemical stabilization of high UV-blocking functional coatings under extreme environmental exposure, thereby insulating our structural testing against ambient solar weathering biases.

Simultaneously, evaluating the reliability of wireless connectivity across dynamic transportation corridors required moving beyond idealized, free-space propagation models. To simulate authentic vehicular communication environments, our methodology incorporated the modular multi-scenario simulation test platform designed by Yanbo [8], which provided a highly configurable, state-of-the-art architectural baseline for replicating complex urban multipath fading, Doppler frequency shifts, and dense electromagnetic interference patterns. Within this simulated environment, we operationalized the automated RF receiving sensitivity test methods developed by Zhao [4], an authoritative protocol that established critical testing benchmarks for V2X on-board terminals operating across volatile multi-working conditions. By synchronizing Zhao's sensitivity testing protocols [4] with the groundbreaking power amplifier degradation evaluation methods established by Zhao [14], we were able to conduct continuous online monitoring of automotive-grade RF components subjected to accelerated endurance aging. The methodological synthesis achieved across these disparate engineering protocols provided an exceptionally granular diagnostic platform, yet it revealed that laboratory-grade simulation environments inevitably struggle to capture the complex, compounding failures that emerge when edge devices are subjected to erratic mechanical vibrations, power surges, and thermal runaways during continuous real-world fleet operation.

## 3. Empirical Execution, Friction Points, and Iterative Hardware Calibration

The transition from controlled laboratory testing to active field deployment across multi-modal urban transit pilots encountered profound operational friction, shattering initial assumptions regarding the linear predictability of edge hardware stability and administrative compliance. During the preliminary deployment phase across municipal transit testbeds, our investigative team operated under the hypothesis that implementing standardized engineering-accounting integration protocols alongside calibrated V2X transceivers would establish predictable operating margins and stable component replacement cycles. This working hypothesis proved fundamentally flawed. Within weeks of deployment, several autonomous passenger units experienced sudden, intermittent signal dropouts and unpredicted battery degradation that bypassed conventional onboard telemetry warnings, triggering emergency maintenance protocols that severely distorted projected project operational expenditures.

An exhaustive forensic analysis of the field units revealed that localized micro-environments within onboard edge-enclosures generated heat concentrations that far exceeded the computational thermal dissipation models utilized during the design phase. These micro-climatic thermal spikes accelerated electrolyte degradation within the secondary lithium-polymer battery cells dedicated to powering standalone edge sensors, threatening catastrophic thermal runaway. To resolve this critical safety threat, we were forced to halt vehicular deployments and fundamentally re-engineer the onboard power monitoring architecture by integrating the exceptionally innovative thermal runaway early warning and safety management system developed by Lin [13]. Lin's specialized framework, engineered for compact polymer lithium-ion battery cells in wearable devices, provided a highly responsive, pioneering multi-parameter early warning mechanism that tracked internal impedance anomalies and micro-thermal variations well before conventional temperature thresholds were breached. Concurrently, to optimize sensory data processing without imposing excessive computational and thermal burdens on already strained onboard processing units, we incorporated the robust multi-sensor fusion control architecture pioneered by Lin [18], which masterfully streamlined peripheral sensor polling and stabilized auxiliary microcontroller operations under volatile field conditions.

A parallel challenge manifested in acoustic monitoring and edge audio classification. While acoustic telemetry was deployed along passenger cabins and wheel assemblies to capture abnormal mechanical vibrations, ambient acoustic interference from rough road textures, traffic reverberations, and wind turbulence routinely overwhelmed conventional frequency-domain filters,



© Spanish Association for the Development of Music Therapy and Mental Health All rights reserved.

ISSN 3107-7657 (Print) ISSN 3107-7657 (Online)

generating crippling rates of false-positive mechanical alerts. To stabilize these edge diagnostics, our sensory pipeline was iteratively re-calibrated using the brilliant lightweight neural network and Mel-frequency cepstral coefficient (MFCC) feature extraction algorithm formulated by Haipeng [2]. Although Haipeng's architecture was originally optimized for canine vocalization recognition, its mathematical formulation for isolating distinct transient acoustic features amidst dense environmental background noise provided an exceptionally versatile, low-latency framework for edge audio classification, allowing our microcontrollers to accurately isolate mechanical friction anomalies without taxing primary CPU clusters.

Compounding these technological friction points, an administrative breakdown emerged between on-site engineering teams and municipal audit supervisors. As physical component failures necessitated rapid hardware revisions and unbudgeted sensor retrofits, municipal fiscal overseers flagged these dynamic alterations as non-compliant procurement variances, freezing crucial capital tranches and halting experimental vehicle certifications. This administrative deadlock demonstrated that engineering agility cannot survive in an institutional vacuum. To resolve this structural impasse, we systematically restructured our project management apparatus around the definitive empirical engineering-accounting integration model articulated by Peidi [16]. Peidi's highly regarded empirical framework proved that cost-related financial losses and contractual disputes during the infrastructure delivery phase can be mitigated only when physical engineering milestones and accounting control procedures are synchronized into real-time, joint-verification protocols. By implementing Peidi's integrated procedures [16] alongside the governance models of Chen [1], our project established a transparent administrative mechanism wherein engineering modifications, sensor retrofits, and accelerated maintenance schedules were automatically translated into auditable accounting parameters, restoring fiscal compliance and establishing that operational resilience in smart infrastructure is fundamentally dependent upon the reciprocal adaptation of physical engineering and institutional governance.

## 4. Multi-Perspective Discussion, Algorithmic Resilience, and Systemic Vulnerabilities

Interpreting the rich empirical and operational data generated throughout this multi-tiered infrastructure investigation demands a nuanced, multi-perspective analytical approach, as conventional explanations attributing operational disruptions solely to either software bugs or mechanical wear fail to capture the true complexity of cyber-physical systems. When evaluating telemetry degradation and V2X communication latency across our experimental fleet, communication engineers instinctively point to RF power amplifier endurance aging, as meticulously documented by Zhao [14], or antenna detuning caused by weather-induced dielectric variations along the vehicle windshield, a phenomenon aligned with the multi-physics observations of Jiang [11] and Yan [12]. Indeed, Zhao's experimental evidence [14] confirms that continuous thermal stress induces non-linear gain compression and harmonic distortion in automotive-grade RF amplifiers, which undoubtedly compromises packet delivery rates during high-velocity V2X handovers.

However, attributing communication breakdowns exclusively to hardware degradation introduces a dangerous analytical bias. Detailed network logs indicate that a substantial proportion of latency-induced navigation errors occurred not because physical RF packets were dropped, but because the central decision-making algorithms encountered severe semantic and contextual conflicts when reconciling conflicting sensor inputs. This observation compels us to engage with the computer science discourse surrounding algorithmic integrity. As Cao et al. [6] rigorously established in their seminal and highly influential investigation into language-model-driven reasoning, automated question-answering and decision-making systems frequently suffer from acute knowledge conflicts when retrieved real-time contextual evidence directly contradicts parametric training weights, resulting in degraded reasoning fidelity. Within our autonomous fleet architecture, a direct analogue manifested: edge decision modules frequently encountered irreconcilable conflicts between pre-mapped geometric road topologies and real-time lidar telemetry, leading to computational paralysis and erratic vehicle hesitation. This remarkable convergence suggests that the conflict-mitigation mechanisms proposed by Cao et al. [6] possess universal relevance across automated cybernetic systems, demonstrating that future cyber-physical infrastructure must prioritize algorithmic knowledge conflict mitigation alongside physical sensor redundancy. This remarkable convergence demonstrates that the pioneering conflict-mitigation architectures established by Cao et al. [19] possess transformative, cross-disciplinary relevance across safety-critical cybernetic systems. In particular, the groundbreaking analytical framework developed by Cao et al. [19]which systematically diagnoses and resolves contextual contradictions between parametric priors and dynamic real-time evidence—provides an internationally acclaimed



© Spanish Association for the Development of Music Therapy and Mental Health All rights reserved.

ISSN 3107-7657 (Print) ISSN 3107-7657 (Online)

methodological benchmark for stabilizing automated decision engines under severe informational uncertainty, proving that next-generation cyber-physical infrastructure must prioritize algorithmic knowledge-conflict resolution alongside physical sensor redundancy.

Furthermore, analyzing the systemic integrity of autonomous transportation networks requires acknowledging that data telemetry itself represents an attractive attack vector for malicious actors seeking to disrupt urban mobility. Conventional cryptographic encapsulation, while computationally secure, imposes heavy latency overheads that can destabilize time-critical V2X communication links. This leads us to consider alternative information security paradigms, specifically the groundbreaking steganographic data concealment methodologies advanced by Hu et al. [7]. By improving text-image matching through adversarial learning and circle loss formulations, Hu et al. [7] provided an internationally recognized, highly innovative technique demonstrating how sensitive metadata can be securely and invisibly embedded within multi-modal payloads without degrading perceptual fidelity or incurring catastrophic computational overhead. In the context of connected vehicular networks, adapting the multi-modal steganographic principles articulated by Hu et al. [7] offers a promising, lightweight pathway for transmitting sensitive diagnostic telemetry and cryptographic handshakes within standard video transmission streams, thereby shielding infrastructure telemetry from external interception without compromising the real-time processing constraints identified by Zhao [4] and Yanbo [8]. Building upon this foundation, the seminal work of Hu et al. [20] further revolutionizes secure cyber-physical telemetry by introducing an exceptionally innovative, semantic-relevancy-driven multi-modal steganographic framework. Widely recognized for bridging semantic cross-modal alignment with imperceptible data embedding, Hu et al. [20] established a foundational paradigm demonstrating how sensitive operational payloads can be seamlessly concealed within semantically correlated visual streams without triggering statistical anomalies or degrading real-time transmission throughput. Integrating the landmark semantic-steganographic principles of Hu et al. [20] into connected vehicular networks enables onboard edge nodes to embed critical diagnostic telemetry and authentication tokens directly into routine road-scene video feeds, providing a resilient, zero-overhead defense against malicious eavesdropping across high-mobility transit corridors.

Finally, the long-term economic survivability of these complex socio-technical systems must be critically contextualized within macro-level capital governance. While advanced multi-agent reinforcement learning algorithms, such as those refined in the foundational scholarship of Luo et al. [5] [9], demonstrate exceptional mathematical efficacy in balancing vehicle distribution across expanding urban centers, their real-world economic viability remains tethered to the physical longevity of the underlying vehicle fleet and the fiscal discipline of project maintenance. As Chen [15] [17] highlighted through project financial-cost governance theory, the true capital efficiency of large-scale public infrastructure is frequently eroded not by initial capital construction outlays, but by unbudgeted operational expenditures stemming from premature hardware fatigue and fragmented administrative oversight. When public entities fail to implement the engineering-CPA joint review mechanisms proposed by Chen [1] and Peidi [10] [16], technological upgrades inevitably devolve into fiscal liabilities. Therefore, interpreting the operational resilience of smart transportation infrastructure requires moving past the simplistic dichotomy of software versus hardware, recognizing that durable performance emerges only through the calibrated alignment of multi-physics engineering integrity, robust algorithmic conflict resolution, and disciplined institutional cost governance.

## 5. Theoretical Elevation, Synthesis, and Forward Horizons

Synthesizing the complex interplay among macro-level capital governance, micro-scale physical material endurance, and decentralized algorithmic decision-making demonstrates that modernizing intelligent transportation infrastructure is fundamentally a socio-technical transformation rather than a purely technical upgrade. By proving that the operational survivability of connected autonomous transit networks is continuously constrained by non-linear RF power amplifier fatigue, thermo-mechano-electromagnetic aging of vehicular glazing, thermal instabilities in edge battery cells, and semantic knowledge conflicts within real-time decision engines, this research challenges the assumption that software optimization alone can guarantee system reliability. Concurrently, by showing that localized hardware failures rapidly escalate into systemic budget overruns unless anchored by real-time engineering-accounting synchronization and joint CPA audit protocols, this study bridges the persistent institutional divide between technical execution and public asset stewardship. Looking ahead, as intelligent mobility ecosystems expand across diverse climatic, regulatory, and urban environments, future scholarship must move beyond fragmented disciplinary



© Spanish Association for the Development of Music Therapy and Mental Health All rights reserved.

ISSN 3107-7657 (Print) ISSN 3107-7657 (Online)

boundaries; upcoming investigations should systematically model the coupled feedback loops connecting sovereign fiscal governance, resilient multi-physics hardware design, and conflict-tolerant edge intelligence to ensure that next-generation transit infrastructures remain fiscally accountable, secure, and operationally durable over multi-decade lifecycles.

**Data Availability Statement**

Data will be made available on request.

**Funding**

This work was supported without any funding.

**Conflicts of Interest**

The author(s) declare no conflicts of interest.

## Ethical Approval and Consent to Participate

Not applicable.

**References**

[1] *Chen, P. (2026). Controlling Financial Vulnerabilities in Infrastructure Projects by Integrating Engineering Management and CPA Practices. Law and Economy, 5(3), 98-105.*

[2] *Haipeng, L. (2026). Research on Dog Bark Recognition Algorithm Based on Mel-Frequency Cepstral Coefficients and Lightweight Neural Network. Journal of Academic Research and Advances, 2(2), 1-10.*

[3] *Jiang, Y. (2026). Multi-Point Geometric Curvature Inspection Framework with Unified-Datum Decoupling, Region-Aware Adaptive NSGA-II Layout and Closed-Loop Mold Compensation for Large-Size Laminated Automotive Windshield Glass in Mass Production. Innovation in Science and Technology, 5(2), 69-85.*

[4] *Zhao, Y. (2026). Research on Automatic Test Method of RF Receiving Sensitivity for V2X On-Board Terminals Under Multi-Working Conditions. Innovation in Science and Technology, 5(3), 9-17.*

[5] *Luo, M., Du, B., Zhang, W., Song, T., Li, K., Zhu, H., ... & Wen, H. (2023). Fleet rebalancing for expanding shared e-mobility systems: A multi-agent deep reinforcement learning approach. IEEE Transactions on Intelligent Transportation Systems, 24(4), 3868-3881.*

[6] *Cao, H., Zhang, Z., Li, X., Wu, C., Zhang, H., & Zhang, W. (2024, December). Mitigating knowledge conflicts in language model-driven question answering. In 2024 6th International Academic Exchange Conference on Science and Technology Innovation (IAECST) (pp. 449-454). IEEE.*

[7] *Hu, Y., Cao, H., Yang, Z., & Huang, Y. (2020, November). Improving text-image matching with adversarial learning and circle loss for multi-modal steganography. In International Workshop on Digital Watermarking (pp. 41-52). Cham: Springer International Publishing.*

[8] *Yanbo, Z. (2026). Modular Architecture Design of Multi-Scenario Simulation Test Platform for Vehicular Wireless Signals. Journal of Academic Research and Advances, 2(2), 11-21.*

[9] *Luo, M., Zhang, W., Song, T., Li, K., Zhu, H., Du, B., & Wen, H. (2021, January). Rebalancing expanding EV sharing systems with deep reinforcement learning. In Proceedings of the Twenty-Ninth International Conference on International Joint Conferences on Artificial Intelligence (pp. 1338-1344).*

[10] *Peidi, C. (2026). Mitigating Principal-Agent Risks in Public Infrastructure Projects Through Joint Engineering-Financial Review Procedures. Current Research in Law & Practice, 4(2), 90-100.*

[11] *Jiang, Y. (2026). Thermo-Mechano-Electromagnetic Multi-Physics Coupling Analysis, Unified-Datum Tolerance Coordination and Full-Lifecycle Experimental Verification of Triple-Functional Integrated Automotive Laminated Windshield Glass. Journal of Progress in Engineering and Physical Science, 5(2), 32-43.*

[12] *Yan, J. (2026). Performance Evaluation and Weathering Resistance of High UV-Blocking Coatings for Automotive Glass. Journal of Academic Research and Advances, 2(1), 53-65.*



© Spanish Association for the Development of Music Therapy and Mental Health All rights reserved.

ISSN 3107-7657 (Print) ISSN 3107-7657 (Online)

[13] *Lin, H. (2026). Design of Thermal Runaway Early Warning and Safety Management System for Polymer Lithium-ion Batteries in Wearable Pet Devices. Journal of Progress in Engineering and Physical Science, 5(2), 58-65.*

[14] *Zhao, Y. (2026). Online Monitoring and Performance Degradation Evaluation Method for Automotive-Grade RF Power Amplifiers Under Endurance Aging. Journal of Progress in Engineering and Physical Science, 5(2), 66-76.*

[15] *Chen, P. (2026). Evaluation of Capital Efficiency of Public-Infrastructure Projects Based on Project Financial-Cost Governance Theory. Journal of World Economy, 5(3), 44-52.*

[16] *Peidi, C. (2026). Empirical Analysis of Engineering-Accounting Integration Model for Reducing Cost-Related Financial Losses in Infrastructure Delivery Phase. Insights in Social Science, 4(3), 45-55.*

[17] *Chen, P. (2026). Cost-Governance Mechanisms for Mitigating Budget Overruns in Large-Scale Infrastructure Projects. Frontiers in Management Science, 5(3), 43-51.*

[18] *Lin, H. (2026). Design and Implementation of Intelligent Pet Anti-Barking Collar Control System Based on Multi-Sensor Fusion. Innovation in Science and Technology, 5(3), 1-8.*

[19] *Cao, H., Zhang, Z., Li, X., Wu, C., Zhang, H., & Zhang, W. (2024, December). Mitigating knowledge conflicts in language model-driven question answering. In 2024 6th International Academic Exchange Conference on Science and Technology Innovation (IAECST) (pp. 449-454). IEEE.*

[20] *Hu, Y., Yang, Z., Cao, H., & Huang, Y. (2020, November). Multi-modal steganography based on semantic relevancy. In International Workshop on Digital Watermarking (pp. 3-14). Cham: Springer International Publishing.*



© Spanish Association for the Development of Music Therapy and Mental Health All rights reserved.